
Direct Metal

Production 3D Printers

3D SYSTEMS

Manufacture Fully Functional Metal Parts in Hours

- Precision laser melting—patented and proven
- Increased productivity, repeatability and flexibility
- Access to a wide range of metals and alloys
- Unmatched design and manufacturing freedom
- Efficient materials and energy management











www.3dsystems.com

MANUFACTURING*THE*FUTURE

Turn market pressure into competitive advantage

Patented and Proven Standard in Direct Metal 3D Printing

Direct Metal production 3D printers are the proven industry standard. You benefit from our experience in addition to:

- Robust manufacturing floor platform
- Patented powder layering system guarantees outstanding quality
- Exceptional surface finish and resolution
- Excellent accuracy and repeatability
- Fully dense parts with superior mechanical properties
- Fast build speeds

Our truly global product support team, with dedicated service and application engineers, allows us to meet your rigorous quality requirements at facilities around the world. In addition we offer a back-up manufacturing service for our customers to handle overflow.



The Process:

The Direct Metal process builds up fully dense, chemically pure metal parts from 3D CAD data by melting fine powder with a laser beam, layer by layer.

With layer sizes ranging from 5–30 microns, there are no limitations to part complexity.

The 3D Systems line of Direct Metal production 3D printers supports particle sizes as low as 5 microns, resulting in better part accuracy, surface finish and feature detail resolution.

Depending on your requirements choose between the following build volumes:

ProX™ 100:	3.9 x 3.9 x 3.1 inches (100 x 100 x 80 mm)
ProX™ 200:	5.5 x 5.5 x 3.9 inches (140 x 140 x 100 mm)
ProX™ 300:	9.8 x 9.8 x 11.8 inches (250 x 250 x 300 mm)

Applications:

When complex metal parts are needed fast, our portfolio of direct metal solutions turns market pressure into competitive advantage in industries like:

- **Aerospace and defense**
- **Engine/component manufacturing**
- **Medical technology**
- **Patient-specific implants (PSI)**
- **Dental applications**
- **Conformal cooling in tooling inserts**
- **Jewelry & objects d'art**

Seamless and intuitive 3D printing software

Software:

Processing: Open and intuitive software enables users to precisely define all key manufacturing parameters and track essential production data.

Manufacturing: Engineered specifically for the low- to mid-volume production of complex metal or ceramic parts.

Dental: A high-performance solution for managing the manufacture of fixed and removable dental prostheses. The user is guided from dental file import to the creation of the manufacturing files; it is seamless and intuitive.



Versatile Metal and Ceramic Materials: Benefit from the materials flexibility of our Direct Metal production 3D printers, including reactive metals and ceramics. Tell us your requirements and our application engineers will define the best material solution for you. We offer a wide choice of standard metal alloys and ceramics, including steel, CrCo, Inconel, Al and Ti alloys.



3D Systems offers software tools specifically designed to ensure your successful direct metal or ceramic manufacturing process.

When it comes to additive manufacturing, the printing system is only one part of the equation. Software integration with the manufacturing process is an important factor when utilising direct metal 3D printing to produce a more cost-effective workflow in the development and production of new products.



Direct Metal

Production 3D Printers

Maximum reliability and repeatability







	ProX 100	ProX 200	ProX 300
Specifications			
Laser power/type	50 W/Fibre laser	300 W/Fibre laser	500 W/Fibre laser
Laser wavelength	1070 nm	1070 nm	1070 nm
Layer thickness range	Adjustable, min10 µm max 50 µm		
Build envelope capacity *(X x Y x Z)*	3.94 x 3.94 x 3.15 in (100 x 100 x 80 mm)	5.51 x 5.51 x 3.94 in (140 x 140 x 100 mm)	9.84 x 9.84 x 11.81 in (250 x 250 x 300 mm)
Metal material choice	Stainless steels, tool steels, non-ferrous alloys, super alloys and others		
Ceramic material choice	Cermet (Al_2O_3; TiO_2) and others	Cermet (Al_2O_3; TiO_2) and others	Cermet (Al_2O_3; TiO_2) and others
Repeatability	x=20 µm, y=20 µm, z=20 µm	x=20 µm, y=20 µm, z=20 µm	x=20 µm, y=20 µm, z=20 µm
Minimum detail resolution	x=100 µm, y=100 µm, z=20 µm	x=100 µm, y=100 µm, z=20 µm	x=100 µm, y=100 µm, z=20 µm
Space Requirements *(W x D x H)*			
Dimensions uncrated	48 x 31 x 77 in (120 x 77 x 195 cm)	48 x 59 x 77 in (120 x 150 x 195 cm)	95 x 87 x 95 in (240 x 220 x 240 cm)
Weight uncrated	2200 lbs (1000 kg)	3300 lbs (approx. 1500 kg)	11000 lbs (approx. 5000 kg)
Electrical Requirements	230V / 2.7 KVA / single phase	400V / 8 KVA / 3 phase	400V / 15 KVA / 3 phase
Compressed Air Requirements	6-8 bar	6-8 bar	6-8 bar
	CE	CE	CE
Control System & Software			
Software tools	Processing - Manufacturing		
Control software	PX Control	PX Control	PX Control
Operating system	Windows XP	Windows XP	Windows XP
Input data file format	STL, IGES, STEP	STL, IGES, STEP	STL, IGES, STEP
Network type and protocol	Ethernet 10 /100 , RJ-45 Plug	Ethernet 10 /100 , RJ-45 Plug	Ethernet 10 /100 , RJ-45 Plug
Accessories			
Recycling system	Optional external system (PX BOX)	Optional external system (PX BOX)	Automatic
Material Handling			
Loading system	Manual	Semiautomatic	Automatic
Certification	CE marked	CE marked	CE marked

3D Systems Corporation
333 Three D Systems Circle
Rock Hill, SC 29730 USA

Telephone: +1 803.326.4080
Toll Free: +1 800.889.2964

Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.

© 2013 by 3D Systems Inc. All rights reserved. Specifications subject to change without notice. ProX is a trademark and the 3D Systems logo and stylized text are registered trademarks of 3D Systems Inc.